GRUNDIG
made for you

DVD RECEIVERS / DVD MICRO SYSTEMS		Cinemo DR 5400 DD	Cinemo DR 4500 DD	Cinemo DR 3400 DD	Scenos UMS 6400 DVD	Scenos UMS 4400 DVD
Amplifier unit						
Dolby Digital 5.1		•	•	•	•	Dolby Digital 2.1
ProLogic / DTS decoder		•/•	•/•	•/•	•/•	–/–
Digital Sound Control		Live House, Hall, Concert, Theatre	Rock, Pop, Classic, Jazz, Ex-Bass	Live House, Hall, Concert, Theatre	Pop, Rock, Jazz, Classic	Pop, Rock, Jazz, Classic
PMPO	W	1300	500	700	560	450
Music output	W	5 x 45; 1 x 100 (Subwoofer)	5 x 20; 1 x 25 (Subwoofer)	5 x 35; 1 x 50 (Subwoofer)	5 x 14	2 x 12
Nominal output	W	5 x 35; 1 x 80 (Subwoofer)	5 x 15; 1 x 20 (Subwoofer)	5 x 25; 1 x 35 (Subwoofer)	5 x 10	2 x 18
Input sensivity / Impedance	mV/kohms	800 / 22	400 / 22	800 / 22	–	–
Loudspeaker impedance	ohms	6 / 10 (Subwoofer)	4 / 3 (Subwoofer)	8 / 4 (Subwoofer)	8	8
DVD unit						
Playable disc formats		DVD-Audio, DVD Video, DVD-R, DVD-RW, CD-Digital Video 1.1 and 2.0, S-VCD, CD-Digital Audio, CD-R, CD-RW, MP3, WMA, JPEG	DVD Video, DVD+R, DVD+RW, DVD-R, DVD-RW, DivX-CD, CD-Digital Video 1.1 und 2.0, S-VCD, CD-Digital Audio, CD-R, CD-RW, MP3, WMA, JPEG	DVD Video, DVD-R, DVD-RW, CD-Digital Video 1.1 and 2.0, S-VCD, CD-Digital Audio, CD-R, CD-RW, MP3, WMA, JPEG	DVD Video, DVD-R, DVD-RW, CD-Digital Video 1.1 and 2.0, S-VCD, CD-Digital Audio, CD-R, CD-RW, MP3, WMA, JPEG	DVD Video, DVD-R, DVD-RW, CD-Digital Video 1.1 and 2.0, S-VCD, CD-Digital Audio, CD-R, CD-RW, MP3, WMA, JPEG
Picture formats		4:3; 16:9	4:3; 16:9	4:3; 16:9	4:3; 16:9	4:3; 16:9
PAL / NTSC playback		•	•	•	•	•
Progressive Scan PAL / NTSC		–	•	–	•	•
On Screen Display (OSD)		•	•	•	•	•
Picture search forward / reverse		•	•	•	•	•
Slow motion / Perfect still picture		•/•	•/•	•/•	•/•	•/•
Repeat		•	•	•	•	•
Language choice (dialog, subtitle)1)		•	•	•	•	•
Multi-angle choice1)		•	•	•	•	•
Tuner unit						
Ranges		FM, MW (AM)	FM	FM, MW (AM)	FM, MW (AM)	FM, MW (AM)
PLL frequency synthesizer		•	•	•	•	•
Station memory		30 + 15	20	30 + 30	20 + 10	20 + 10
Radio Data System RDS		•	•	•	•	•
FM range	MHz	87,5...108	87,5...108	87,5...108	87,5...108	87,5...108
AM (MW) range	MHz	522 ...1629	–	522 ...1629	522 ... 1629	522 ... 1629
Connections						
Inputs		TV/SAT, VCR, VCR2, FM-antenna (75 Ohm), AM-antenna, digital (koaxial)	TV/SAT, VCR, FM-antenna (75 Ohm)	TV/SAT, VCR, FM-antenna (75 Ohm), AM-antenna, digital (optical)	TV/SAT, FM-antenna (75 Ohm), AM-antenna	TV/SAT, FM-antenna (75 Ohm), AM-antenna
Outputs		Digital (optical), TV, speaker, Subwoofer Preamp, Video (composite), VCR, S-Video, headphones	Digital (coaxial), TV, YUV (Progressive Scan), speaker, Video (composite), VCR, S-Video, headphones	Digital (optical), TV, speaker, VCR, S-Video, headphones	Line/Aux, digital (koaxial), VCR (composite), S-Video, YUV (Progressive Scan), Preamp out 5.1, headphones	Line/Aux, digital (koaxial), VCR (composite), S-Video, YUV (Progressive Scan), headphones
Remote control		•	•	•	•	•
Mains supply, mains frequency	V~, Hz	230, 50/60	230, 50/60	230, 50/60	230, 50/60	230, 50/60
Power consumption max. / standby	approx. W	410 / 1	120 / 3	340 / 1	20 / 9 (0,5 ECO-Mode)	60 / 5 (0,5 ECO-Mode)
Dimensions (W x H x D)	approx. cm	36 x 7 x 38.5	43 x 5 x 31	36 x 8 x 38	15.2 x 15.7 x 26	15.2 x 15.7 x 26
Supplied accessories		AV-cable, speaker cable, remote control	AV-cable, speaker cable, remote control	AV-cable, speaker cable, remote control	AV-cable, speaker cable, remote control Subwoofer system cable	AV-cable, speaker cable, remote control

LOUDSPEAKER SET Front-/ Rear-/ Center-Speaker						
Acoustic principle		closed, 1 wide band magnetic shielded	1-way bassreflex Front and center speaker magnetic shielded	closed, 1 wide band magnetic shielded	closed, 1 wide band, magnetic shielded	2-way bassreflex
Nominal capacity	Watt	35	15	25	10	12
Music capacity	Watt	45	25	35	15	18
Nominal impedance	Ohm	6	4	8	8	8
Transmission range	Hz	150 – 20.000	150 – 20.000	150 – 20.000	150 – 20000	150 – 20000
Dimensions (W x H x D)	cm	9 x 12 x 13	9 x 9.4 x 9.5	9 x 13 x 13	9 x 13 x 9.6	16 x 27 x 20
Subwoofer						
Acoustic principle		1-way bassreflex, passiv	1-way bassreflex, passiv	1-way bassreflex, passiv	1-way bassreflex, active	1-way bassreflex, active
Nominal capacity	W	80	25	35	50 nominal capacity	30 nominal capacity
Music capacity	W	100	35	50	70 music capacity	45 music capacity
Nominal impedance	Ohm	10	3	4	>10000	>10000
Transmission range	Hz	40 –150	40 –150	40 –150	40 –150	40 –150
Mains supply, mains frequency	V~, Hz	–	–	–	230, 50/60	230, 50/60
Power consumption max. / standby	approx. W	–	–	–	115 / 0,5	85 / 5
Dimensions (W x H x D)	approx. cm	18.5 x 38 x 32.5	12 x 33.5 x 27.5	16.5 x 33 x 33.5	20 x 32.5 x 41	20 x 31 x 34

Technical data supplied without liability.